

Operating Instructions



5' Propane Grill

Note: Always follow all safety instructions affixed to this grill. Follow all local codes when using this grill.

1. Attach the propane tank (or tanks) to the grill using the attachment hanging from the side of the grill.
2. Ensure propane tanks or tanks are installed and secured correctly.
3. Turn all burner knobs and the red runner tube knob(s) fully clockwise to the "off" position.
4. **Slowly** open the propane tank valve. (This step is where most problems are caused)
5. Push and turn the runner tube KNOB (RED KNOB OR KNOBS) fully counter-clockwise to the "on" position.
6. Insert a lit match or suitable ignition device through an oblong hole in the front panel.
7. Ensure the entire runner tube is lit using the sight holes on the front panel between burner knobs.
8. Open desired burner valves (BLACK KNOBS). Ensure that the burners light entirely from the runner tube.
9. Remember to fill the drip pan(s) with $\frac{3}{4}$ " of water.

Note: On average, you will use 2 pounds of propane per burner per hour.

To shut down:

1. Turn all knobs clockwise to the "off" position.
2. Shut off the main gas or close tank valves.
3. Disconnect propane.

Caution:

- If the runner tube does not correctly provide or stay lit, shut off the gas supply. Wait at least 5 minutes before attempting to re-light
- DISCONNECT THE GAS LINE FROM GRILL, THEN RECONNECT!
- If burners or runner tubes fail to light or remain lit, shut off, disconnect gas, and discontinue use.

**For any questions or concerns, be sure to contact us immediately.
Thank you for your business!**

1155 Route 9
Wappingers Falls, NY
(845) 298-0011



1 Precision Road
Danbury, CT
(203) 744-2295