

# Operating Instructions



# Dunk Tank

- **Be sure to review ALL safety rules before use.**
  - You must always have adult supervision when the tank is in use.
  - Never leave a dunk tank filled with water un-attended
  - Cordon off a "danger zone" in front, sides, and behind the tank. Keep people out of the zone to avoid getting hit by an errant or deflected throw. Children should never be allowed inside this "danger zone."
  - You must be at least 5 feet tall and no more than 250 pounds to enter the tank.
  - No non-swimmers in dunk tank.
  - Keep the dunk tank away from electricity.
  - Keep the water level at least 8" away from the top of the tank.
  - Only one person is on the seat and never stand on the seat.
  - Before each use, ensure the seat is securely locked, and the safety latch is engaged.
  - Always wear shoes with rubber soles to keep from slipping.
  - Advise participants to move towards the front of the tank to avoid hitting their head on the seat when coming out of the water.
  - Do not operate a dunk tank during a storm.
  - Never use baseballs or other hard balls on the tank. Do not hit the target with your hands.
  - **Note:** When filled tank weighs over 4,500 pounds
1. Select a level area for set-up.
  2. Slowly lift and set the tank upright.
  3. Swing the gate wing from its stored position to be perpendicular to the tank.
  4. Lower the stabilizing rod on the bottom of the wing, so the wind does not move it, as this will cause the trigger arm to jam.
  5. Check the drain plug to ensure it is tight, then fill it with water.
  6. Place the flattened end of the arm into the trigger mechanism. Put the other end through the square tubing on the wing and the hole in the canvas. Ensure the arm drops into the slot on the side of the frame.
  7. Insert the target into the end of the arm so the pinholes line up. Insert the clip pin.
  8. Place one hand on the front of the seat and push down. On the other hand, test the target to see that it works properly.
  9. Adjust the difficulty by positioning the arm slightly closer or further from the ball thrower.

## Takedown:

1. Remove the drain plug and let the tank empty. Replace plug.
2. Fold the wing against the side of the unit and securely tie it off.
3. Place the seat in the "up" position and lock.

**For any questions or concerns, be sure to contact us immediately.**

**Thank you for your business!**

1155 Route 9  
Wappingers Falls, NY  
(845) 298-0011



1 Precision Road  
Danbury, CT  
(203) 744-2295